







025mm

## Recessed round LED downlight - 2W - Osram Chip - UGR18 - Cutout Ø 25mm - Black

2W circular LED downlight equipped with Osram LED chip and Lifud driver. It stands out for its low glare index (UGR<18) and high color rendering index (CRI>90), providing high-quality and efficient lighting. Available in warm white tone (2700K).



| Product data   |   |
|--|---|
| Housing color  | White (use), Black (use)  |
| Light temperature  | 2700°K (use)  |
| Opening angle (°)  | 38  |
| Certs  | CE, ROHS  |
| Energy efficiency class  | G   |
| CRI  | 90-95   |
| Dimensions (mm) LxWxH  | Ø 30 X 30, Ø 30x30  |
| Cutting dimensions (mm)  | Ø 25  |
| Dimmable   | No  |
| Driver   | External, Lifud   |
| Form   | Circular  |
| Guarantee  | According to legal warranty: 3 years                                |
| IP   | IP20  |
| Kelvin (K)   | 2700  |
| Lumens (Lm)  | 42  |
| Material   | Aluminum  |
| Material diffuser  | Polycarbonate   |
| Assembly   | Recessed  |
| Orientable   | No  |
| Power (W)  | 2   |
| Sensor   | No  |
| Nominal Voltage (V)  | 220 - 240 V AC  |
| Кеу  | Extra warm white  |
| UGR  | UGR18   |
| Outdoor Use  | No  |
| Recommended UseHotels, Commerce, Living room, Museums - Galleries, Fashion | and retail, Wardrobes, Jewelry, Furniture, Wineries and wine stores |





| Product variants<br>Reference | Attributes   |  |
|-------------------------------|--|--|
| B1225-R-B-270                 | Housing color: White (use), Light temperature : 2700°K (use) |  |
| B1225-R-N-270                 | Housing color: Black (use), Light temperature : 2700°K (use) |  |