

Recessed round LED downlight - 12W - UGR18 - Cutout Ø 70mm - White

Ref. B1227-12W-B-270


LED circular downlight composed of 7 lights with a total power of 12W. Incorporates CREE LED chips. It stands out for its low glare index (UGR<18) and high color rendering index (CRI>90), providing high-quality and efficient lighting. Available in warm white tone (2700K).





Product data

Housing color	White (use)
Light temperature	2700°K (use)
Opening angle (°)	38
Certs	CE, ROHS
Energy efficiency class	G
CRI	90-95
Dimensions (mm) LxWxH	Ø79 x 50.5
Cutting dimensions (mm)	Ø70
Dimmable	No
Driver	External
Guarantee	According to legal warranty: 3 years
IP	IP20
IP Kelvin (K)	IP20 2700
Kelvin (K)	2700
Kelvin (K) Lumens (Lm)	2700 755
Kelvin (K) Lumens (Lm) Material	2700 755 Aluminum
Kelvin (K) Lumens (Lm) Material Material diffuser	2700 755 Aluminum Polycarbonate
Kelvin (K) Lumens (Lm) Material Material diffuser Assembly	2700 755 Aluminum Polycarbonate Recessed
Kelvin (K) Lumens (Lm) Material Material diffuser Assembly Orientable	2700 755 Aluminum Polycarbonate Recessed No
Kelvin (K) Lumens (Lm) Material Material diffuser Assembly Orientable Power (W)	2700 755 Aluminum Polycarbonate Recessed No





UGR	UGR18
Outdoor Use	No
Service life (h)	25,000

Product variants

Reference Attributes



B1227-12W-B-270 Housing color: White (use), Light temperature : 2700°K (use)