





Recessed Backlight LED panel - 120x60cm - 5600lm - Philips driver - 50W - UGR22 - IP40

The Philips LED Backlight panel with driver features backlight or backlit technology, which combines innovative optical and mechanical design characteristics to achieve high-efficiency, uniform illumination with minimal glare (UGR 22). Available in neutral white (4000K), warm white (3000K), and cool white (6000K), it has a power of 50W and a luminous flux of 5600 lumens. Its high color rendering index, CRI>80, allows it to reproduce colors very similarly to natural light. ** 5 Year Warranty **



Product data

Light temperature	3000°K, 4000°K, 6000K
Opening angle (°)	120
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	1195 x 595 x 32
LED Panel Dimensions	120x60
Dimmable	No
Driver	Philips
Efficiency (Lm/w)	135
Power factor (cosφ)	0.9
Guarantee	5 years
IP	IP40
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	5600
Assembly	Recessed
Orientable	No
Power (W)	50
Sensor	No
LED Technology	BACKLIT - BACKLIGHT
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white



UGR	UGR22
Outdoor Use	No
Recommended Use	Hotels, Offices
Service life (h)	25,000

Product variants

Reference	Attributes	
B5234-BACKLIGHT-BC	Light temperature : 3000°K	
B5234-BACKLIGHT-BF	Light temperature : 6000K	
B5234-BACKLIGHT-BN	Light temperature : 4000°K	