

KIT Aro round downlight Ø85mm + LED Module MR16 5W

Product data

Light temperature 3000°K (use), 4000°K (use), 6000K (use)
 Housing color White (use), Black (use), White and Gold (use), White and Silver (to use), Black and White (use), White and Silver (to use)

Product variants

Reference	Attributes
K930-75-R-B-B1355-BC	Light temperature : 3000°K (use), Housing color: White (use)
K930-75-R-B-B1355-BF	Light temperature : 6000K (use), Housing color: White (use)
K930-75-R-B-B1355-BN	Light temperature : 4000°K (use), Housing color: White (use)
K930-75-R-BD-B1355-BC	Light temperature : 3000°K (use), Housing color: White and Gold (use)
K930-75-R-BD-B1355-BF	Light temperature : 6000K (use), Housing color: White and Gold (use)
K930-75-R-BD-B1355-BN	Light temperature : 4000°K (use), Housing color: White and Gold (use)
K930-75-R-BN-B1355-BC	Light temperature : 3000°K (use), Housing color: Black and White (use)
K930-75-R-BN-B1355-BF	Light temperature : 6000K (use), Housing color: Black and White (use)
K930-75-R-BN-B1355-BN	Light temperature : 4000°K (use), Housing color: Black and White (use)
K930-75-R-BP-B1355-BC	Light temperature : 3000°K (use), Housing color: White and Silver (to use)

<i>Reference</i>	<i>Attributes</i>
K930-75-R-BP-B1355-BF	Light temperature : 6000K (use), Housing color: White and Silver (to use)
K930-75-R-BP-B1355-BN	Light temperature : 4000°K (use), Housing color: White and Silver (to use)
K930-75-R-BR-B1355-BC	Light temperature : 3000°K (use), Housing color: White and Red (use)
K930-75-R-BR-B1355-BF	Light temperature : 6000K (use), Housing color: White and Red (use)
K930-75-R-BR-B1355-BN	Light temperature : 4000°K (use), Housing color: White and Red (use)
K930-75-R-N-B1355-BC	Light temperature : 3000°K (use), Housing color: Black (use)
K930-75-R-N-B1355-BF	Light temperature : 6000K (use), Housing color: Black (use)
K930-75-R-N-B1355-BN	Light temperature : 4000°K (use), Housing color: Black (use)