







Kit 150cm waterproof LED batten + 24W LED T8 tube - 6000K

Ref. K8470-150-6K

 $Waterproof screen kit 150cm + 1 \, LED \, tube \, 24W. \, The polycarbonate screen is resistant and durable, ideal for humid and outdoor environments. \, The \, 24W \, LED \, tube, in cool white tone (6000K), is made of nano PVC. \, It offers an exceptional luminous efficiency of 136lm/W, providing powerful and uniform lighting for various applications.$



Product data

Certs CE, ROHS Energy efficiency class E Dimensions (mm) LxWxH 1565x64.4x60 Dimmable No Guarantee According to legal warranty: 3 years IP IP65 Kelvin (K) 6000 Material Polycarbonate Material diffuser Polycarbonate Assembly Surface Power (W) 24 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED SMD 2835 Type of tube T8 Key Cold white Outdoor Use If Recommended Use Industry, Parking	Сар	G13
Dimensions (mm) LxWxH Dimmable Ro Guarantee According to legal warranty: 3 years IP IP65 Kelvin (K) 6000 Material Polycarbonate Material diffuser Polycarbonate Assembly Surface Power (W) 24 Sensor No Nominal Voltage (V) Type of LED SMD 2835 Type of tube T8 Key Cold white Outdoor Use	Certs	CE, ROHS
DimmableNoGuaranteeAccording to legal warranty: 3 yearsIPIP65Kelvin (K)6000MaterialPolycarbonateMaterial diffuserPolycarbonateAssemblySurfacePower (W)24SensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 2835Type of tubeT8KeyCold whiteOutdoor UseIf	Energy efficiency class	E
Guarantee According to legal warranty: 3 years IP IP65 Kelvin (K) 6000 Material Polycarbonate Material diffuser Polycarbonate Assembly Surface Power (W) 24 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED SMD 2835 Type of tube T8 Key Cold white Outdoor Use	Dimensions (mm) LxWxH	1565x64.4x60
IPIP65Kelvin (K)6000MaterialPolycarbonateMaterial diffuserPolycarbonateAssemblySurfacePower (W)24SensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 2835Type of tubeT8KeyCold whiteOutdoor UseIf	Dimmable	No
Kelvin (K)6000MaterialPolycarbonateMaterial diffuserPolycarbonateAssemblySurfacePower (W)24SensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 2835Type of tubeT8KeyCold whiteOutdoor UseIf	Guarantee	According to legal warranty: 3 years
MaterialPolycarbonateMaterial diffuserPolycarbonateAssemblySurfacePower (W)24SensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 2835Type of tubeT8KeyCold whiteOutdoor UseIf	IP	IP65
Material diffuserPolycarbonateAssemblySurfacePower (W)24SensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 2835Type of tubeT8KeyCold whiteOutdoor UseIf	Kelvin (K)	6000
Assembly Surface Power (W) 24 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED SMD 2835 Type of tube T8 Key Cold white Outdoor Use If	Material	Polycarbonate
Power (W) 24 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED SMD 2835 Type of tube T8 Key Cold white Outdoor Use	Material diffuser	Polycarbonate
SensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 2835Type of tubeT8KeyCold whiteOutdoor UseIf	Assembly	Surface
Nominal Voltage (V) Type of LED SMD 2835 Type of tube T8 Key Cold white Outdoor Use	Power (W)	24
Type of LED SMD 2835 Type of tube T8 Key Cold white Outdoor Use If	Sensor	No
Type of tube T8 Key Cold white Outdoor Use If	Nominal Voltage (V)	220 - 240 V AC
KeyCold whiteOutdoor UseIf	Type of LED	SMD 2835
Outdoor Use If	Type of tube	Т8
	Key	Cold white
Recommended Use Industry, Parking	Outdoor Use	lf
	Recommended Use	Industry, Parking





Product variants

Reference Attributes



K8470-150-6K