






Outdoor LED Downlight 5W - 4000K - IP65 - TRIAC dimmable - Interchangeable bezel - Cutout Ø68mm

5W LED Downlight in warm white color (3000K) ideal for outdoors or areas with potential humidity (IP65). It stands out for its compact and elegant design in white, offering an excellent lighting option for any space. Customize your appearance with polycarbonate decorative rings, available in three finishes: matte black, silver, and chrome. These rings are sold separately and offer greater versatility to adapt to different decorative styles. Provides high-quality lighting, with a high color rendering index (CRI>80) and a brightness of 420 lumens. Adjustable by TRIAC for intensity control.



Product data

Light temperature	3000°K, 4000°K, 6500K
High	35mm, 40mm
Width	Ø87mm, Ø86mm
Beam angle (°)	100
Certs	CE, ROHS
Energy efficiency class	F
CRI	80-85
Cutting dimensions (mm)	Ø68mm
Dimmable	Yes
Form	Circular
Frequency (Hz)	50 - 60
Warranty	According to legal warranty: 3 years
Warranty	According to legal warranty: 3 years
IP	IP65
IP Kelvin (K)	IP65 3000, 4000
IP Kelvin (K) Lumens (Lm)	IP65 3000, 4000 420, 460
IP Kelvin (K) Lumens (Lm) Material	IP65 3000, 4000 420, 460 Polycarbonate
IP Kelvin (K) Lumens (Lm) Material Material diffuser	IP65 3000, 4000 420, 460 Polycarbonate Polycarbonate
IP Kelvin (K) Lumens (Lm) Material Material diffuser Assembly	IP65 3000, 4000 420, 460 Polycarbonate Polycarbonate Recessed
IP Kelvin (K) Lumens (Lm) Material Material diffuser Assembly Orientable	IP65 3000, 4000 420, 460 Polycarbonate Polycarbonate Recessed No





Nominal Voltage (V)	220 - 240 V AC
Key	Warm white, Neutral white
Outdoor Use	Yes
Recommended Use	Hotels, Kitchens, Commerce, Balconies, Bathrooms
Driver	Internal

Product variants

Reference Attributes



BD25-5W-TRIAC-3K Light temperature : 3000°K



BD25-5W-TRIAC-4K Light temperature : 4000°K



BD25-5W-TRIAC-6K Light temperature : 6500K