


KIT - Recessed square downlight ring 93x93mm (white/black) + 5.4W GU10 Bulb + Socket

Complete lighting kit composed of: Adjustable square downlight with low UGR - White color with champagne interior. GU10 5.4W LED Bulb - Available in 3 shades: warm white, neutral, and cool Pre-wired GU10 lamp holders made of ceramic.



Product data

Housing color	White and champagne (use), Black and champagne (use), Black and White (use), Gray and White (use), Gray and Black (use)
Light temperature	2700°K, 4000°K, 6000K
Cap	GU10
Certs	CE, ROHS
Dimensions (mm) LxWxH	93 x 93 x 29
Cutting dimensions (mm)	Ø75, Ø 75
Efficiency (Lm/w)	130
Warranty	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	4000, 6000, 2700
Kit	Yes
Material	Polycarbonate, Lightbulb: Glass
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	Yes
Key	Warm white, Cold white, Neutral white
Outdoor Use	No
Recommended Use	Dining room, Bedrooms, Hotels, Kitchens, Commerce
Power (W)	5.4



Product variants

Reference	Attributes
K921-CB-BC	Housing color: White and champagne (use), Light temperature : 2700°K



Reference	Attributes	
K921-CB-BF	Housing color: White and champagne (use), Light temperature : 6000K	
K921-CB-BN	Housing color: White and champagne (use), Light temperature : 4000°K	
K921-CN-BC	Housing color: Black and champagne (use), Light temperature : 2700°K	
K921-CN-BF	Housing color: Black and champagne (use), Light temperature : 6000K	
K921-CN-BN	Housing color: Black and champagne (use), Light temperature : 4000°K	
K921-GB-BC	Housing color: Gray and White (use), Light temperature : 2700°K	
K921-GB-BF	Housing color: Gray and White (use), Light temperature : 6000K	
K921-GB-BN	Housing color: Gray and White (use), Light temperature : 4000°K	

Reference	Attributes	
K921-GN-BC	Housing color: Gray and Black (use), Light temperature : 2700°K	
K921-GN-BF	Housing color: Gray and Black (use), Light temperature : 6000K	
K921-GN-BN	Housing color: Gray and Black (use), Light temperature : 4000°K	
K921-NB-BC	Housing color: Black and White (use), Light temperature : 2700°K	
K921-NB-BF	Housing color: Black and White (use), Light temperature : 6000K	
K921-NB-BN	Housing color: Black and White (use), Light temperature : 4000°K	