

LED CCT 1-phase track spotlight - 35W - ZOOM 20°- 60° - CRI 90


35W LED Projector for Single-Phase Track with a compact and modern design. It is orientable and features zoom to adjust the light angle between 20° and 60°. Includes CCT system for adjusting the color temperature (3000K-4000K-6000K). High color accuracy (CRI>90), perfect for commercial lighting.** 5-Year Warranty **



Product data

High 255mm Width Ø95mm Opening angle (°) 20° - 60° Certs CE, ROHS Energy efficiency class F CRI 90-95 Dimmable No Driver KGP Guarantee 5 years IP IP20 Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT Outdoor Use No	Housing color	White (use), Black (use)
Opening angle (°) 20° - 60° Certs CE, ROHS Energy efficiency class F CRI 90-95 Dimmable No Driver KGP Guarantee 5 years IP IP20 Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	High	255mm
Certs CE, ROHS Energy efficiency class F CRI 90-95 Dimmable No Driver KGP Guarantee 5 years IP IP20 Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Width	Ø95mm
Energy efficiency class F CRI 90-95 Dimmable No Driver KGP Guarantee 5 years IP IP20 Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Opening angle (°)	20° - 60°
CRI 90-95 Dimmable No Driver KGP Guarantee 5 years IP IP20 Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Certs	CE, ROHS
Dimmable No Driver KGP Guarantee 5 years IP IP20 Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Energy efficiency class	F
Driver KGP Guarantee 5 years IP IP20 Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	CRI	90-95
Guarantee 5 years IP IP20 Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Dimmable	No
IP IP20 Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Driver	KGP
Kelvin (K) 3000, 4000, 6000 Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Guarantee	5 years
Long 191mm Lumens (Lm) 3000 Material Aluminum Material diffuser Polycarbonate Orientable Yes Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	IP	IP20
Lumens (Lm)3000MaterialAluminumMaterial diffuserPolycarbonateOrientableYesPower (W)35SensorNoNominal Voltage (V)220 - 240 V ACTrack TypeSingle-phaseType of LEDChip BridgeluxKeyCCT	Kelvin (K)	3000, 4000, 6000
MaterialAluminumMaterial diffuserPolycarbonateOrientableYesPower (W)35SensorNoNominal Voltage (V)220 - 240 V ACTrack TypeSingle-phaseType of LEDChip BridgeluxKeyCCT	Long	191mm
Material diffuserPolycarbonateOrientableYesPower (W)35SensorNoNominal Voltage (V)220 - 240 V ACTrack TypeSingle-phaseType of LEDChip BridgeluxKeyCCT	Lumens (Lm)	3000
OrientableYesPower (W)35SensorNoNominal Voltage (V)220 - 240 V ACTrack TypeSingle-phaseType of LEDChip BridgeluxKeyCCT	Material	Aluminum
Power (W) 35 Sensor No Nominal Voltage (V) 220 - 240 V AC Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Material diffuser	Polycarbonate
SensorNoNominal Voltage (V)220 - 240 V ACTrack TypeSingle-phaseType of LEDChip BridgeluxKeyCCT	Orientable	Yes
Nominal Voltage (V) Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Power (W)	35
Track Type Single-phase Type of LED Chip Bridgelux Key CCT	Sensor	No
Type of LED Chip Bridgelux Key CCT	Nominal Voltage (V)	220 - 240 V AC
Key CCT	Track Type	Single-phase
·	Type of LED	Chip Bridgelux
Outdoor Use No	Key	ССТ
	Outdoor Use	No

Recommended UseHotels, Commerce, Restaurants, Museums - Galleries, Fashion and retail





Product variants

Reference Attributes



BPM-35W-ZOOM-CCT-B

Housing color: White (use)



BPM-35W-ZOOM-CCT-N

Housing color: Black (use)