









KIT - Recessed downlight ring Ø93mm (silver) + 5.4W GU10 Bulb + Socket


Complete lighting kit composed of: Fixed recessed trim \emptyset 93mm with low UGR - Black color with a golden interior. 5.4W GU10 LED Bulb - Available in 3 shades: warm white, neutral, and cool GU10 lamp holders made of pre-wired ceramic.



Pr		_1		-4	_1	_	4 -	
P^{r}	'n	п	11	c_{T}	п	п	TA	
	\mathbf{v}	ч	и	UL.	м	ч	LUI	

Housing color	White, Black, Silver (to use), Gold
Light temperature	3000°K, 4000°K, 6000K
Beam angle (°)	100
Сар	GU10
Certs	CE, ROHS
Dimensions (mm) LxWxH	Aro: 93x53mm, Ø93x53
Cut distance (mm)	Ø85
Efficiency (Lm/w)	130
Warranty	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	4000, 6000, 2700
Kit	Yes
Material	Polycarbonate, Lightbulb: Glass
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Key	Warm white, Cold white, Neutral white
UGR	UGR18
Power (W)	5.4
Outdoor Use	No





Product variants



Reference	Attributes	
K987-B-BC	Housing color: White, Light temperature : 3000°K	
K987-B-BF	Housing color: White, Light temperature : 6000K	
K987-B-BN	Housing color: White, Light temperature : 4000°K	
K707-D-BIN	riousing color. Writte, Light temperature . 4000 K	
K987-D-BC	Housing color: Gold , Light temperature : 3000°K	
		Ц
K987-D-BF	Housing color: Gold , Light temperature : 6000K	
K987-D-BN	Housing color: Gold , Light temperature : 4000°K	
K987-N-BC	Housing color: Black, Light temperature : 3000°K	



Reference	Attributes	
K987-N-BF	Housing color: Black, Light temperature : 6000K	
K987-N-BN	Housing color: Black, Light temperature : 4000°K	
K987-P-BC	Housing color: Silver (to use), Light temperature : 3000°K	
K987-P-BF	Housing color: Silver (to use), Light temperature : 6000K	
K987-P-BN	Housing color: Silver (to use), Light temperature : 4000°K	