









KIT - Recessed downlight ring Ø93mm (silver) + 5.4W GU10 Bulb + Socket


Complete lighting kit composed of: Fixed recessed trim \emptyset 93mm with low UGR - Black color with a golden interior. 5.4W GU10 LED Bulb - Available in 3 shades: warm white, neutral, and cool GU10 lamp holders made of pre-wired ceramic.



Pro	- J-	4	-d -	-4-
$\Gamma \Gamma \Gamma$	JUι	166	uu	ıLU

Housing color	White (use), Black (use), Silver (to use), Gold (to use)	
Light temperature	3000°K (use), 4000°K (use), 6000K (use)	
Opening angle (°)	100	
Сар	GU10	
Certs	CE, ROHS	
Dimensions (mm) LxWxH	Aro: 93x53mm, Ø93x53	
Cut distance (mm)	Ø85	
Efficiency (Lm/w)	130	
Guarantee	According to legal warranty: 3 years	
IP	IP20	
Kelvin (K)	4000, 6000, 2700	
Kit	Yes	
Material	Polycarbonate, Lightbulb: Glass	
Material diffuser	Polycarbonate	
Assembly	Recessed	
Orientable	No	
Key	Warm white, Cold white, Neutral white	
UGR	UGR18	
Power (W)	5.4	
Outdoor Use	No	





Product variants



Reference	Attributes	
K987-B-BC	Housing color: White (use), Light temperature : 3000°K (use)	
K987-B-BF	Housing color: White (use), Light temperature : 6000K (use)	
K987-B-BN	Housing color: White (use), Light temperature : 4000°K (use)	
K987-D-BC	Housing color: Gold (to use), Light temperature : 3000°K (use)	
K987-D-BF	Housing color: Gold (to use), Light temperature : 6000K (use)	
K987-D-BN	Housing color: Gold (to use), Light temperature : 4000°K (use)	
K987-N-BC	Housing color: Black (use), Light temperature : 3000°K (use)	



Reference	Attributes	
K987-N-BF	Housing color: Black (use), Light temperature : 6000K (use)	
K987-N-BN	Housing color: Black (use), Light temperature : 4000°K (use)	
	Housing cool. Sheek (use, Eight temperature: 1000 K (use)	
K987-P-BC	Housing color: Silver (to use), Light temperature : 3000°K (use)	
K987-P-BF	Housing color: Silver (to use), Light temperature : 6000K (use)	
K987-P-BN	Housing color: Silver (to use), Light temperature : 4000°K (use)	