




Modern Pendant Light "Roomba" - 10W - CCT -White

The modern pendant lamp "Roomba" 10W combines a minimalist design in black finish with a golden interior. It features a retractable cable, allowing it to be installed as a ceiling fixture or as a pendant lamp. With the CCT system to adjust color temperature, it is ideal for elegant and versatile lighting.



Product data

Housing colorWrite (use), black (use), black (use)WidthØ74mmOpening angle (°)38CertsCE, ROHSEnergy efficiency classECRI90-95DimmableNoDriverKGPGuarantee5 yearsIPIP20Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCTOutdoor UseNo	Housing color	White (use), Black (use), Black and Gold (use)
Opening angle (°)38CertsCE, ROHSEnergy efficiency classECRI90-95DimmableNoDriverKGPGuarantee5 yearsIPIP20Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT		
CertsCE, ROHSEnergy efficiency classECRI90-95DimmableNoDriverKGPGuarantee5 yearsIPIP20Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT		
Energy efficiency classECRI90-95DimmableNoDriverKGPGuarantee5 yearsIPIP20Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT		
CRI90-95DimmableNoDriverKGPGuarantee5 yearsIPIP20Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT		
DimmableNoDriverKGPGuarantee5 yearsIPIP20Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Energy efficiency class	E
DriverKGPGuarantee5 yearsIPIP20Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	CRI	90-95
Guarantee5 yearsIPIP20Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Dimmable	No
IPIP20Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Driver	KGP
Kelvin (K)3000, 4000, 6000Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Guarantee	5 years
Long1660 mm, 1666 mmLumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	IP	IP20
Lumens (Lm)990MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Kelvin (K)	3000, 4000, 6000
MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Long	1660 mm, 1666 mm
Material diffuserPolycarbonateAssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Lumens (Lm)	990
AssemblySurface, SuspensionOrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Material	Aluminum
OrientableNoPower (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Material diffuser	Polycarbonate
Power (W)10SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Assembly	Surface, Suspension
SensorNoNominal Voltage (V)220 - 240 V ACKeyCCT	Orientable	No
Nominal Voltage (V)220 - 240 V ACKeyCCT	Power (W)	10
Key CCT	Sensor	No
	Nominal Voltage (V)	220 - 240 V AC
Outdoor Use No	Кеу	ССТ
	Outdoor Use	No





Recommended Use

Dining room, Bedrooms, Hotels, Restaurants, Living room

Product variants

Reference

BPC-10W-CCT-B

Housing color: White (use)

Attributes

BPC-10W-CCT-ND

Housing color: Black and Gold (use)