


Pendant/Surface Mounted LED CCT Linear light - 60W - Adjustable power - 180cm

60W LED Linear Light with a modern design for suspended or surface installation. Provides high-quality lighting (CRI>80) and low glare (UGR<19). With CCT system to adjust the color temperature (3000K/4000K/5000K). Adjustable power. Available in 2 colors: white and black. Includes suspension installation kit.



Product data

High 65mm Width 50mm Opening angle (°) 120 CRI 80-85 Guarantee 5 years Kelvin (K) 3000, 4000, 5000 Long 1800mm Lumens (Lm) 5100 Material Aluminum Material diffuser Polycarbonate Assembly Surface, Suspension Power (W) 60 Nominal Voltage (V) 220 - 240 V AC Type of LED CHIP San'an Key CCT UGR UGR19	Housing color	White (use), Black (use)
Opening angle (°) 120 CRI 80-85 Guarantee 5 years Kelvin (K) 3000, 4000, 5000 Long 1800mm Lumens (Lm) 5100 Material Aluminum Material diffuser Polycarbonate Assembly Surface, Suspension Power (W) 60 Nominal Voltage (V) 220 - 240 V AC Type of LED CHIP San'an Key CCT	High	65mm
CRI 80-85 Guarantee 5 years Kelvin (K) 3000, 4000, 5000 Long 1800mm Lumens (Lm) 5100 Material Aluminum Material diffuser Polycarbonate Assembly Surface, Suspension Power (W) 60 Nominal Voltage (V) 220 - 240 V AC Type of LED CHIP San'an Key CCT	Width	50mm
Guarantee 5 years Kelvin (K) 3000, 4000, 5000 Long 1800mm Lumens (Lm) 5100 Material Aluminum Material diffuser Polycarbonate Assembly Surface, Suspension Power (W) 60 Nominal Voltage (V) 220 - 240 V AC Type of LED CHIP San'an Key CCT	Opening angle (°)	120
Kelvin (K) 3000, 4000, 5000 Long 1800mm Lumens (Lm) 5100 Material Aluminum Material diffuser Polycarbonate Assembly Surface, Suspension Power (W) 60 Nominal Voltage (V) 220 - 240 V AC Type of LED CHIP San'an Key CCT	CRI	80-85
Long1800mmLumens (Lm)5100MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionPower (W)60Nominal Voltage (V)220 - 240 V ACType of LEDCHIP San'anKeyCCT	Guarantee	5 years
Lumens (Lm)5100MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionPower (W)60Nominal Voltage (V)220 - 240 V ACType of LEDCHIP San'anKeyCCT	Kelvin (K)	3000, 4000, 5000
MaterialAluminumMaterial diffuserPolycarbonateAssemblySurface, SuspensionPower (W)60Nominal Voltage (V)220 - 240 V ACType of LEDCHIP San'anKeyCCT	Long	1800mm
Material diffuserPolycarbonateAssemblySurface, SuspensionPower (W)60Nominal Voltage (V)220 - 240 V ACType of LEDCHIP San'anKeyCCT	Lumens (Lm)	5100
Assembly Surface, Suspension Power (W) 60 Nominal Voltage (V) 220 - 240 V AC Type of LED CHIP San'an Key CCT	Material	Aluminum
Power (W) 60 Nominal Voltage (V) 220 - 240 V AC Type of LED CHIP San'an Key CCT	Material diffuser	Polycarbonate
Nominal Voltage (V)220 - 240 V ACType of LEDCHIP San'anKeyCCT	Assembly	Surface, Suspension
Type of LED CHIP San'an Key CCT	Power (W)	60
Key CCT	Nominal Voltage (V)	220 - 240 V AC
	Type of LED	CHIP San'an
UGR UGR19	Key	ССТ
	UGR	UGR19





Product variants

Reference Attributes

40W

B9025-180-B Housing color: White (use)



B9025-180-N Housing color: Black (use)