








GU10 LED Bulb - 5W - 120°

GU10 LED dichroic bulb ideal for replacing conventional halogens up to 50W, with energy consumption savings of up to 85%. Incorporates SMD2835 LED chips that emit high-quality light, "no flicker," with a power of 5W. Available in 4 shades: Extra warm white: 2700K - 556 Im Warm white: 3000K - 524 Im Neutral white: 4000K - 602 Im Cool white: 6000K - 553 Im



Product data

| Light temperature | 2700°K, 3000°K, 4000°K, 6000K |
|--|---|
| Width | Ø50mm |
| Beam angle (°) | 120 |
| Сар | GU10 |
| Certs | CE, ROHS |
| Energy efficiency class | F |
| CRI | 80-85 |
| Dimmable | No |
| Driver | Internal |
| Power factor (cosφ) | 0.5, 0.6 |
| Frequency (Hz) | 50 - 60 |
| Marranty | |
| Warranty | According to legal warranty: 3 years |
| IP | According to legal warranty: 3 years IP20 |
| • | |
| IP | IP20 |
| IP Kelvin (K) | IP20 3000, 4000, 6000, 2700 |
| IP Kelvin (K) Long | IP20 3000, 4000, 6000, 2700 55mm |
| IP Kelvin (K) Long Lumens (Lm) | IP20 3000, 4000, 6000, 2700 55mm 524, 553, 556, 602 |
| IP Kelvin (K) Long Lumens (Lm) Material diffuser | IP20 3000, 4000, 6000, 2700 55mm 524, 553, 556, 602 Plastic |
| IP Kelvin (K) Long Lumens (Lm) Material diffuser Power (W) | IP20 3000, 4000, 6000, 2700 55mm 524, 553, 556, 602 Plastic |
| IP Kelvin (K) Long Lumens (Lm) Material diffuser Power (W) Temperature range | IP20 3000, 4000, 6000, 2700 55mm 524, 553, 556, 602 Plastic 5 -20°F ~ +40°F |





Outdoor Use
Service life (h)
25,000

Product variants
Reference
Attributes

B51-PAR16GU10-120-5W-270
Light temperature: 2700°K

B51-PAR16GU10-120-5W-BC
Light temperature: 6000K



BS1-PAR16GU10-120-5W-BN Light temperature : 4000°K